

# MODEL 630



## Medical Sealer for Critical Packaging Environments

*This Precision Medical Sealer incorporates all the requisite features to become an integral part of your Medical Product Validation process.*

### PROTECTED

Fully lock-out protected and Alarmed Digital process Controls provide you the confidence that all process parameters are maintained seal-to-seal. NEMA 4 rated Stainless Steel enclosure, controls, and hardware withstand the harshest anti-microbial agents.

### PRECISION

Designed for in situ calibration. Now, you can be confident that all calibrated controls stay that way. The calibration ports are external for easy access during calibration and validation.

The Model 630 is delivered to you with the confidence that you'll receive the perfect seal each and every time giving you maximum product integrity and sterility.

### SOLUTIONS

- Ergonomic design allows for unparalleled ease of use during IQ, OQ, and PQ as well as during change over and production.
- Operator lock-out for maximum productivity without compromising process control.



MEDICAL SEALER

MODEL 630

ACCU-MED SEALER

**BUILT-IN FEATURES**

- Digital Control of:
  - Seal Temperature
  - Seal Time
  - Seal Pressure (analog regulator with digital readout)
- Calibration Ports for:
  - Seal Temperature
  - Seal Time
  - Seal Pressure
- Visible and Audible Alarms for:
  - (Require Supervisor Override)
  - Cold Seal Temperature Profile
  - Seal Temperature with Settable High & Low Alarms
  - Jaw Obstruction
  - Seal Pressure with Settable High & Low Alarms
- Additional Safety Features:
  - Emergency Stop
  - Safe, Low-Force Jaw Close
- Production Enhancing Features:
  - High Force Seal Jaw
  - Upper Heat Element
  - New Ergonomic Case Design
  - NEMA 4, Welded Stainless Steel Case
  - Product Support Tray
  - External Exhaust Port

**SPECIFICATIONS**

- Seal Widths: 3/8" Standard  
Other seal widths and styles also available
- Seal Lengths: 15", 20", 25", 30" or 35"
- Requirements:
  - Power: 120 Vac, 7 Amps (15 x 3/8")
  - Air: 1.0 CFM @ 80 PSI
- Size: Length: Seal Length +5.5"  
Width - 12"  
Height - 8"
- Approximate Weight: 26 - 40 lbs.

**FACTORY OPTIONS**

- Initial Calibration
- 220 Vac Conversion
- CE Certification

**OPTIONAL ACCESSORIES**

- Ergonomic Multi-Position Accu-Seal Stand
- Ultra Quiet Lab/Office Compressor
- Standard Industrial Air Compressor
- Portable Accu-Sealer Cart



**TWO-YEAR LIMITED WARRANTY**

The Accu-Seal Model 630 was designed, built, and tested to give years of reliable, trouble free service.



OPTIONAL PORTABLE ACCU-SEALER CART (SHOWN W/INDUSTRIAL COMPRESSOR)



OPTIONAL ERGONOMIC MULTI-POSITION ACCU-SEAL STAND (SHOWN W/ MODEL 635-232)



OPTIONAL ULTRA-QUIET LAB/OFFICE COMPRESSOR



225 Bingham Drive, Suite B  
San Marcos, CA 92069  
800-452-6040 • 760-591-9800  
FAX 760-591-9117  
www.accu-seal.com  
e-mail: info@accu-seal.com